

CD60A电动机起动电容器



铝壳、胶木壳或者ABS外壳，双插片及电缆引出。体积小容量大、损耗小、性能稳定。
Aluminum shell, bakelite shell or ABS shell, double insert and cable lead-out. Small volume, large capacity, small loss, stable performance.

产品特征:		Product Character:
本产品体积小，使用寿命长，自愈性好，具有防爆介质层的特点.它是特殊的格栅，是理想的节能，以防止大电流冲击。		This product is characterized by its small volume, long life-time, good self-
技术数据:		Technical Data:
气候类型25/70/21		Climate type 25/70/21
电容限+/-5%+/-10%		Capacitance tolerance +/-5%, +/-10%
绝缘电阻≥3000 mΩ		Insulation resistance ≥3000MΩ
在引出端到外壳≥1000 mΩ之间		between leading-out end and shell ≥ 1000MΩ

损耗切 $Tg\delta \leq 0.002(50/100\text{ Hz})$		Loss tangent $tg\delta \leq 0.002(50/100\text{Hz})$	
技术数据:			
性能标准	GB/T3667.2-2008/IEC 60252-2: 2003		
气候类型	$-10^{\circ}\text{C} \sim +55^{\circ}\text{C}$		
额定电压	110~330 VAC		
标准电容和容限	50~1500 $\mu\text{F}(-10\%+20\%)$		
损失切线	0~+20%		
耐久性	+55°C, 110~165 VAC, 1s, 59s, 30000次后		
	+55°C, 220~330 VAC, 1s, 关59s, 15000次后		
终端间耐压	1.2倍工作电压, 2s内不发生故障		
主机与外壳之间的耐压	200 VAC 60秒, 不发生故障		

尺寸(毫米)			
电容(UF)	100-165 VAC	200-250 VAC	300-330 VAC
21-25	36*70	36*70	36*70
25-30	36*70	36*70	36*70
30-36	36*70	36*70	36*70
36-43	36*70	36*70	36*70
43-52	36*70	36*70	36*70
47-56	36*70	36*70	36*70
53-64	36*70	36*70	36*70
64-77	36*70	36*70	36*70
72-88	36*70	36*70	36*70
88-108	36*70	36*70	46*86

108-130	36*70	36*70	46*86
124-140	36*70	36*70	46*86
130-156	36*70	36*70	46*86
145-174	36*70	36*70	46*86
161-193	36*70	36*70	46*86
189-227	36*70	46*86	52*111
216-259	46*86	46*86	52*111
223-280	46*86	46*86	52*111
243-292	46*86	46*86	52*111
270-324	46*86	46*86	52*111
324-389	46*86	46*86	52*111
340-408	46*86	46*86	52*111
378-454	46*86	46*86	52*111
400-480	46*86	46*86	52*111
430-515	46*86	46*86	52*111
460-552	46*86	46*86	52*111
540-648	46*111	52*111	52*111
890-708	46*111	52*111	52*111
645-774	46*111	52*111	52*111
708-850	46*111	52*111	52*111
720-850	46*111	52*111	52*111
720-865	46*111	52*111	65*111
800-960	52*111	52*111	65*111
815-978	52*111	52*111	65*111
829-995	52*111	52*111	65*111
850-1020	52*111	52*111	65*111

